THERMOBREAK No-Clad FOIL TAPE



- Fire rated to Class 0 under BS476 parts 6 & 7
- UV & salt water resistant reinforced aluminium foil
- High initial tack





THERMOBREAK No-Clad FOIL TAPE

Thermobreak[®] No-Clad Foil Tape is a specially developed UV and salt water resistant reinforced aluminium foil tape designed to handle outdoor conditions and ensure the integrity of the Thermobreak[®] No-Clad insulation system. It has exceptional initial tack to provide quick installation on all Thermobreak[®] No-Clad insulation joints.

Size & Packaging

75mm wide x 50m long	8 rolls / carton
Carton Dimensions: 300 mm (L) x 300 mm (W) x 170 mm (H)	



Technical Specifications



Property	Typical Value	Test Method
Foil Thickness	9 micron	Internal
Tensile Strength	106 N/25mm MD 77 N/25mm CD	ISO 1421
Elongation	35.8% MD 48.4% CD	ISO 1421
Adhesive Thickness	150 micron	Internal
Service Temperature	-40 / +80 °C	Internal
Adhesion to Steel	1.3 kg/25mm	PSTC 3
Initial Tack	1.7cm	PSTC 6
Holding Power	> 24 hours	PSTC 7
Emissivity	≤0.05	ASTM E408
Flammability Class 0	Class 0	BS 476 Parts 6 and 7
Water Vapour Permeance	< 2.9 ng/Ns	ASTM E96
UV Resistance	Excellent	ISO 4892:3

Thermobreak® is a registered trademark of Sekisui Chemical Co. Ltd. or its subsidiaries





Distributed by:

Australian Plant

Tel:

1-5 Parraweena Rd, PO Box 2898,

+61 2 9525 9880

Email: info@sekisuifoam.com.au

Web: www.thermobreak.com

Taren Point NSW 2229 Australia



PT KREASI SOLUSI INDOPRIMA Aeropolis Technopark Blok WH CS.48 Jl. Marsekal Surya Darma, Neglasari Tangerang, Banten – 15129 Telp: 021 – 5958 8131

 Thailand Plant

 700/379
 Moo 6, Tumbol Donhua-loh,

 Amphur Muang Chonburi 20000
 Tel:

 +66 38 213219~26
 Email:

 Email:
 info@thaisekisui.co.th

 Web:
 www.thermobreak.com